

General Description

These N-channel MOSFET are produced using advanced Magnachip's MOSFET Technology, which provides low on-state resistance, high switching performance and excellent quality.


These devices are suitable device for SMPS, high Speed switching and general purpose applications.

Features

- $V_{DS} = 600V$
- $I_D = 3.5A$
- $R_{DS(ON)} \leq 2.0\Omega$ @ $V_{GS} = 10V$

Applications

- Power Supply
- PFC
- High Current, High Speed Switching



Absolute Maximum Ratings ($T_a = 25^\circ C$)

Characteristics	Symbol	Rating	Unit	
Drain-Source Voltage	V_{DSS}	600	V	
Gate-Source Voltage	V_{GSS}	± 30	V	
Continuous Drain Current	I_D	$T_C=25^\circ C$	3.5	A
		$T_C=100^\circ C$	2.2	A
Pulsed Drain Current ⁽¹⁾	I_{DM}	14	A	
Power Dissipation	P_D	$T_C=25^\circ C$	67.5	W
		Derating above 25°C	0.54	W/°C
Repetitive Avalanche Energy ⁽¹⁾	E_{AR}	6.75	mJ	
Peak Diode Recovery dv/dt ⁽³⁾	dv/dt	4.5	V/ns	
Single Pulse Avalanche Energy ⁽⁴⁾	E_{AS}	170	mJ	
Junction and Storage Temperature Range	T_J, T_{stg}	-55~150	°C	

* I_D limited by maximum junction temperature

Thermal Characteristics

Characteristics	Symbol	MDD4N60	Unit
Thermal Resistance, Junction-to-Ambient ⁽¹⁾	R_{thja}	110	°C/W
Thermal Resistance, Junction-to-Case ⁽¹⁾	R_{thjc}	1.85	

Ordering Information

Part Number	Marking	Temp. Range	Package	Packing	RoHS Status
MDD4N60RH	MDD4N60	-55~150°C	TO-252(DPAK)	Reel and Tape	Halogen Free

Electrical Characteristics (T_a =25°C)

Characteristics	Symbol	Test Condition	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	I _D = 250μA, V _{GS} = 0V	600	-	-	V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250μA	3.0	-	5.0	
Drain Cut-Off Current	I _{DSS}	V _{DS} = 600V, V _{GS} = 0V	-	-	1	μA
Gate Leakage Current	I _{GSS}	V _{GS} = ±30V, V _{DS} = 0V	-	-	100	nA
Drain-Source ON Resistance	R _{DS(ON)}	V _{GS} = 10V, I _D = 1.75A		1.7	2.0	Ω
Forward Transconductance	g _{fs}	V _{DS} = 30V, I _D = 1.75A	-	4	-	S
Dynamic Characteristics						
Total Gate Charge	Q _g	V _{DS} = 480V, I _D = 4.0A, V _{GS} = 10V ⁽³⁾	-	12.1		nC
Gate-Source Charge	Q _{gs}		-	3.5		
Gate-Drain Charge	Q _{gd}		-	4.4		
Input Capacitance	C _{iss}	V _{DS} = 25V, V _{GS} = 0V, f = 1.0MHz	-	506	660	pF
Reverse Transfer Capacitance	C _{rss}		-	2.3	3	
Output Capacitance	C _{oss}		-	58	75	
Turn-On Delay Time	t _{d(on)}	V _{GS} = 10V, V _{DS} = 300V, I _D = 4.0A, R _G = 25Ω ⁽³⁾	-	12		ns
Rise Time	t _r		-	20		
Turn-Off Delay Time	t _{d(off)}		-	27		
Fall Time	t _f		-	20		
Drain-Source Body Diode Characteristics						
Maximum Continuous Drain to Source Diode Forward Current	I _S		-	4.6	-	A
Source-Drain Diode Forward Voltage	V _{SD}	I _S = 4.0A, V _{GS} = 0V	-		1.4	V
Body Diode Reverse Recovery Time	t _{rr}	I _F = 4.0A, di/dt = 100A/μs ⁽³⁾	-	243		ns
Body Diode Reverse Recovery Charge	Q _{rr}		-	1.5		μC

Note :

- Pulse width is based on R_{thjc} & R_{thja} and the maximum allowed junction temperature of 150°C.
- Pulse test: pulse width ≤300μs, duty cycle ≤2%, pulse width limited by junction temperature T_{J(max)}=150°C.
- I_{SD} ≤4.0A, di/dt ≤200A/μs, V_{DD}=50V, R_G =25Ω, Starting T_J=25°C
- L=17.9mH, I_{AS}=4.0A, V_{DD}=50V, R_G =25Ω, Starting T_J=25°C,




Fig.1 On-Region Characteristics




Fig.2 On-Resistance Variation with Drain Current and Gate Voltage




Fig.3 On-Resistance Variation with Temperature




Fig.4 Breakdown Voltage Variation vs. Temperature




Fig.5 Transfer Characteristics




Fig.6 Body Diode Forward Voltage Variation with Source Current and Temperature




Fig.7 Gate Charge Characteristics




Fig.8 Capacitance Characteristics




Fig.9 Maximum Safe Operating Area




Fig.10 Transient Thermal Response Curve




Fig.11 Single Pulse Maximum Power Dissipation





Fig.12 Maximum Drain Current vs. Case Temperature

Physical Dimension

TO-252 (DPAK)

Dimensions are in millimeters, unless otherwise specified



Symbol	Min.	Nom.	Max.
E	6.35	-	6.73
L	1.40	1.52	1.78
L1	2.74 REF		
L2	0.508 BCS		
L3	0.89	-	1.27
L4	-	-	1.02
L5	1.14	-	1.52
D	5.97	6.10	6.22
H	9.40	-	10.41
b	0.64	-	0.89
b2	0.76	-	1.14
b3	4.95	-	5.46
e	2.286 BSC		
A	2.18	-	2.39
A1	-	-	0.13
c	0.46	-	0.61
c2	0.46	-	0.89
D1	5.21	-	-
E1	4.32	-	-
⌀	0.00	-	10.00

DISCLAIMER:

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Magnachip reserves the right to change the specifications and circuitry without notice at any time. Magnachip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Magnachip product.  Magnachip is a registered trademark of Magnachip Semiconductor Ltd.