

### General Description

The MDF9N50F uses advanced Magnachip's MOSFET Technology, which provides low on-state resistance, high switching performance and excellent quality.


MDF9N50F is suitable device for SMPS, HID and general purpose applications.

### Features

- $V_{DS} = 500V$
- $I_D = 8.0A$  @  $V_{GS} = 10V$
- $R_{DS(ON)} \leq 0.9\Omega$  @  $V_{GS} = 10V$

### Applications

- Power Supply
- HID
- Lighting



### Absolute Maximum Ratings ( $T_a = 25^\circ C$ )

Characteristics		Symbol	Rating	Unit
Drain-Source Voltage		$V_{DSS}$	500	V
Gate-Source Voltage		$V_{GSS}$	$\pm 30$	V
Continuous Drain Current	$T_c=25^\circ C$	$I_D$	8.0	A
	$T_c=100^\circ C$		4.8	A
Pulsed Drain Current <sup>(1)</sup>		$I_{DM}$	32	A
Power Dissipation	$T_c=25^\circ C$	$P_D$	38	W
	Derate above 25 °C		0.3	W/°C
Peak Diode Recovery $dv/dt$ <sup>(3)</sup>		$Dv/dt$	4.5	V/ns
Single Pulse Avalanche Energy <sup>(4)</sup>		$E_{AS}$	300	mJ
Junction and Storage Temperature Range		$T_J, T_{stg}$	-55~150	°C

\* Id limited by maximum junction temperature

### Thermal Characteristics

Characteristics		Symbol	Rating	Unit
Thermal Resistance, Junction-to-Ambient <sup>(1)</sup>		$R_{\theta JA}$	62.5	°C/W
Thermal Resistance, Junction-to-Case <sup>(1)</sup>		$R_{\theta JC}$	3.3	

## Ordering Information







Part Number	Marking	Temp. Range	Package	Packing	RoHS Status
MDF9N50FTH	MDF9N50F	-55~150°C	TO-220F	Tube	Halogen Free


## Electrical Characteristics ( $T_a = 25^\circ\text{C}$ )

Characteristics	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static Characteristics</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$	500	-	-	V
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250\mu\text{A}$	2.5	-	4.5	
Drain Cut-Off Current	$I_{DS(0)}$	$V_{DS} = 500\text{V}, V_{GS} = 0\text{V}$	-	-	10	$\mu\text{A}$
Gate Leakage Current	$I_{GSS}$	$V_{GS} = \pm 30\text{V}, V_{DS} = 0\text{V}$	-	-	100	nA
Drain-Source ON Resistance	$R_{DS(\text{ON})}$	$V_{GS} = 10\text{V}, I_D = 4.0\text{A}$		0.75	0.9	$\Omega$
Forward Transconductance	$g_f$	$V_{DS} = 30\text{V}, I_D = 4.0\text{A}$	-	4.2	-	S
<b>Dynamic Characteristics</b>						
Total Gate Charge	$Q_g$	$V_{DS} = 400\text{V}, I_D = 8.0\text{A}, V_{GS} = 10\text{V}^{(3)}$	-	16.3	-	nC
Gate-Source Charge	$Q_{gs}$		-	5.8	-	
Gate-Drain Charge	$Q_{gd}$		-	6.1	-	
Input Capacitance	$C_{iss}$	$V_{DS} = 25\text{V}, V_{GS} = 0\text{V}, f = 1.0\text{MHz}$	-	781	-	pF
Reverse Transfer Capacitance	$C_{rss}$		-	1.83	-	
Output Capacitance	$C_{oss}$		-	96.1	-	
Turn-On Delay Time	$t_{d(on)}$	$V_{GS} = 10\text{V}, V_{DS} = 250\text{V}, I_D = 8.0\text{A}, R_G = 25\Omega^{(3)}$	-	20.0	-	ns
Rise Time	$t_r$		-	47.5	-	
Turn-Off Delay Time	$t_{d(off)}$		-	28.0	-	
Fall Time	$t_f$		-	24.0	-	
<b>Drain-Source Body Diode Characteristics</b>						
Maximum Continuous Drain to Source Diode Forward Current	$I_S$		-	8.0	-	A
Source-Drain Diode Forward Voltage	$V_{SD}$	$I_S = 8.0\text{A}, V_{GS} = 0\text{V}$	-	-	1.4	V
Body Diode Reverse Recovery Time	$t_{rr}$	$I_F = 8.0\text{A}, dI/dt = 100\text{A}/\mu\text{s}^{(3)}$	-	94.5	-	ns
Body Diode Reverse Recovery Charge	$Q_{rr}$		-	0.24	-	$\mu\text{C}$


Note :

1. Pulse width is based on  $R_{\text{EJC}}$  &  $R_{\text{EJA}}$  and the maximum allowed junction temperature of  $150^\circ\text{C}$ .
2. Pulse test: pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ , pulse width limited by junction temperature  $T_{J(\text{MAX})}=150^\circ\text{C}$ .
3.  $I_{SD} \leq 8.0\text{A}$ ,  $dI/dt \leq 200\text{A}/\mu\text{s}$ ,  $V_{DD}=50\text{V}$ ,  $R_g=25\Omega$ , Starting  $T_J=25^\circ\text{C}$
4.  $L=6.5\text{mH}$ ,  $I_{AS}=8.0\text{A}$ ,  $V_{DD}=50\text{V}$ ,  $R_g=25\Omega$ , Starting  $T_J=25^\circ\text{C}$







**Fig.7 Gate Charge Characteristics**




**Fig.8 Capacitance Characteristics**




**Fig.9 Maximum Safe Operating Area**



**Fig.10 Maximum Drain Current vs. Case Temperature**



**Fig.11 Transient Thermal Response Curve**




**Fig.12 Single Pulse Maximum Power Dissipation**

## Physical Dimensions

### TO-220F

Dimensions are in millimeters unless otherwise specified



Symbol	Min	Nom	Max
A	4.50		4.93
b	0.63		0.91
b1	1.15		1.47
C	0.33		0.63
D	15.47		16.13
E	9.60		10.71
e		2.54	
F	2.34		2.84
G	6.48		6.90
L	12.24		13.72
L1	2.79		3.67
Q	2.52		2.96
Q1	3.10		3.50
ØR	3.00		3.55

**DISCLAIMER:**

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Magnachip reserves the right to change the specifications and circuitry without notice at any time. Magnachip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Magnachip product.  Magnachip is a registered trademark of Magnachip Semiconductor Ltd.