




# MDT14N043RH

Single N-channel Trench MOSFET 135V 4.3mΩ 201A

## General description

The MDT14N043RH uses advanced Magnachip's MOSFET technology, which provides high performance in on-state resistance, fast switching performance, and excellent quality.

These devices can also be utilized in industrial applications such as high power drives of E-Vehicles(E-bike), DC/DC converter and BMS, general purpose applications.



## Features and benefits


- Magnachip's MOSFET Technology
- Very low on-resistance  $R_{DS(on)}$
- 100% Avalanche /  $R_g$  /  $\Delta V_{DS}$  Tested

## Applications

- Motor Inverter
- Battery Management
- Power Inverter

## Key performance parameters

$V_{DS}$	135	V
$R_{DS(on), max}$	0.0043	$\Omega$
$I_D$	201	A
$Q_G$	137	nC
Junction temperature <sub>max</sub>	175	$^{\circ}C$



## Ordering information

Type / Ordering Code	Package	Marking	Packing	RoHS Status
MDT14N043RH	TOLL	MDT14N043	Tape & Reel	Halogen Free

<http://www.magnachip.com>

**Maximum ratings**, at  $T_J = 25^\circ\text{C}$ , unless otherwise specified

Parameter		Symbol	Rating	Unit
Drain-source Voltage		$V_{DS}$	135	V
Gate-source Voltage		$V_{GS}$	$\pm 20$	V
Drain current	$T_C=25^\circ\text{C}$ Silicon Limited	$I_D$	201	A
	$T_C=100^\circ\text{C}$ Silicon Limited		142	A
<sup>1)</sup> Pulsed drain current	$T_C=25^\circ\text{C}$	$I_{DM}$	804	A
Total power dissipation	$T_C=25^\circ\text{C}$	$P_{tot}$	469	W
	$T_C=100^\circ\text{C}$		234	W
<sup>2)</sup> Avalanche energy, single pulse		$E_{AS}$	450	mJ
Operating and storage temperature		$T_j, T_{stg}$	- 55 ~ 175	$^\circ\text{C}$

**Thermal characteristics**

Parameter		Symbol	Rating	Unit
Thermal resistance, junction - case		$R_{\theta JC}$	0.32	$^\circ\text{C}/\text{W}$
<sup>3)</sup> Thermal resistance, junction - ambient		$R_{\theta JA}$	40	$^\circ\text{C}/\text{W}$

**Notes**

- Pulse width limited by  $T_{jmax}$
- EAS is tested at starting  $T_J = 25^\circ\text{C}$ ,  $L = 1.0\text{mH}$ ,  $I_{AS} = 30\text{A}$ ,  $V_{DD} = 50\text{V}$ ,  $V_{GS} = 10\text{V}$
- Surface mounted FR-4 board by JEDEC (jesd51-7)

Electrical Characteristics ( $T_J = 25^\circ\text{C}$ )

## Static characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Drain-source breakdown voltage	$V_{(BR)DSS}$	135	-	-	V	$V_{GS}=0\text{ V}$ , $I_D=250\ \mu\text{A}$
Gate threshold voltage	$V_{GS(th)}$	2.5	-	3.9	V	$V_{DS}=V_{GS}$ , $I_D=250\ \mu\text{A}$
Zero gate voltage drain current	$I_{DSS}$	-	-	1	$\mu\text{A}$	$V_{DS}=135\text{ V}$ , $V_{GS}=0\text{ V}$
Gate-source leakage current	$I_{GSS}$	-	-	$\pm 100$	nA	$V_{GS}=\pm 20\text{ V}$ , $V_{DS}=0\text{ V}$
Drain-source on-state resistance	$R_{DS(on)}$	-	3.6	4.3	m $\Omega$	$V_{GS}=10\text{ V}$ , $I_D=100\text{ A}$
Gate resistance	$R_G$	-	3.0	-	$\Omega$	$f=1\text{ MHz}$
Transconductance	$g_{fs}$	-	120	-	S	$V_{DS}=10\text{ V}$ , $I_D=100\text{ A}$

## Dynamic characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Input capacitance	$C_{iss}$	-	10,008	-	pF	$V_{GS}=0\text{ V}$ , $V_{DS}=70\text{ V}$ , $f=1\text{ MHz}$
Output capacitance	$C_{oss}$	-	916	-	pF	$V_{GS}=0\text{ V}$ , $V_{DS}=70\text{ V}$ , $f=1\text{ MHz}$
Reverse transfer capacitance	$C_{rfs}$	-	20	-	pF	$V_{GS}=0\text{ V}$ , $V_{DS}=70\text{ V}$ , $f=1\text{ MHz}$
Turn-on delay time	$t_{d(on)}$	-	41	-	ns	$V_{DD}=70\text{ V}$ , $V_{GS}=10\text{ V}$ , $I_D=100\text{ A}$ , $R_{G,ext}=3\ \Omega$
Rise time	$t_r$	-	22	-	ns	$V_{DD}=70\text{ V}$ , $V_{GS}=10\text{ V}$ , $I_D=100\text{ A}$ , $R_{G,ext}=3\ \Omega$
Turn-off delay time	$t_{d(off)}$	-	101	-	ns	$V_{DD}=70\text{ V}$ , $V_{GS}=10\text{ V}$ , $I_D=100\text{ A}$ , $R_{G,ext}=3\ \Omega$
Fall time	$t_f$	-	22	-	ns	$V_{DD}=70\text{ V}$ , $V_{GS}=10\text{ V}$ , $I_D=100\text{ A}$ , $R_{G,ext}=3\ \Omega$

## Gate charge characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Gate to source charge	$Q_{gs}$	-	52	-	nC	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$
Gate charge at threshold	$Q_{gs(th)}$	-	46	-	nC	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$
Gate to drain charge	$Q_{gd}$	-	27	-	nC	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$
Switching charge	$Q_{sw}$	-	40	-	nC	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$
Gate charge total	$Q_g$	-	137	-	nC	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$
Gate plateau voltage	$V_{plateau}$	-	4.8	-	V	$V_{DD}=70\text{ V}$ , $I_D=100\text{ A}$ , $V_{GS}=0\text{ to }10\text{ V}$

## Source-drain diode

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Diode continuous forward current	$I_S$	-	-	201	A	-
Diode pulse current	$I_{S,pulse}$	-	-	804	A	pulsed; $t_p \leq 10\ \mu\text{s}$
Diode forward voltage	$V_{SD}$	-	1.0	1.2	V	$V_{GS}=0\text{ V}$ , $I_F=100\text{ A}$
Reverse recovery time	$t_{rr}$	-	137	-	ns	$I_F=100\text{ A}$ , $dI_F/dt=100\text{ A}/\mu\text{s}$
Reverse recovery charge	$Q_{rr}$	-	540	-	nC	$I_F=100\text{ A}$ , $dI_F/dt=100\text{ A}/\mu\text{s}$

Electrical characteristics diagrams




Fig. 1. On-Region Characteristics




Fig. 2. On-Resistance vs. Drain Current and Gate Voltage




Fig. 3. On-Resistance vs. Junction Temperature




Fig. 4. On-Resistance vs. Gate to Source Voltage




Fig. 5. Transfer Characteristics




Fig. 6. Source-Drain Diode Forward Voltage

Electrical characteristics diagrams




Fig. 7. Gate Charge




Fig. 8. Capacitance




Fig. 9. Safe Operating Area, Junction-to-Ambient




Fig. 10. Maximum Drain vs. Case Temperature





Fig. 11. Thermal Transient Impedance, Junction-to-Ambient

# Package information

TOLL




Symbol	Dimension (mm)		
	Min	Nom	Max
A	2,20	-	2,40
b	0,70	-	0,90
b1	9,70	-	9,90
b2	0,42	-	0,50
c	0,40	-	0,60
D	10,28	-	10,58
D2	3,10	3,30	3,50
E	9,70	9,90	10,10
E1	7,90	8,10	8,30
e	BSC 1,20		
H	11,48	11,68	11,90
H1	BSC 6,95		
J	BSC 3,15		
K1	3,98	4,18	4,38
L	1,38	1,60	1,80
L1	0,60	0,70	0,80
L2	0,50	0,60	0,70
L4	1,00	1,15	1,30
$\theta$	4°	7°	10°

## Notes

Package body size, length and width do not include mold flash, protrusions and gate burrs.

**DISCLAIMER :**

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Magnachip reserves the right to change the specifications and circuitry without notice at any time. Magnachip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Magnachip product.  Magnachip is registered trademarks of Magnachip Semiconductor Ltd.