

General Description


This IGBT is produced using advanced Magnachip's Field Stop Trench IGBT Technology, which provides low $V_{CE(sat)}$, low switching loss performance and excellent quality.

Features

- High ruggedness
- $V_{CE(sat)}$ positive temperature coefficient
- Very soft, fast recovery anti-parallel diode
- Maximum junction temperature 175°C

Applications

- UPS
- Welder
- General inverter



Package outline and symbol

- G : Gate
- C : Collector
- E : Emitter

Absolute Maximum Ratings

Characteristics		Symbol	Rating	Unit
Collector-emitter voltage		V_{CES}	650	V
Gate-emitter voltage		V_{GE}	±20	V
DC collector current, t_p limited by T_{vjmax}	$T_C=25^\circ\text{C}$	I_C	76.0	A
	$T_C=100^\circ\text{C}$		50.5	A
Pulsed collector current, t_p limited by T_{vjmax}		I_{Cpuls}	150	A
Diode forward current, t_p limited by T_{vjmax}	$T_C=25^\circ\text{C}$	I_F	62.8	A
	$T_C=100^\circ\text{C}$		38.7	A
Diode pulsed current, t_p limited by T_{vjmax}		I_{Fpuls}	150	A
Total power dissipation	$T_C=25^\circ\text{C}$	P_{tot}	273	W
	$T_C=100^\circ\text{C}$		136	W
Short circuit withstand time $V_{CC} \leq 400\text{V}$, $V_{GE} = 15\text{V}$, $T_C = 150^\circ\text{C}$		t_{SC}	5	μs
Operating Junction temperature range		T_{vj}	-40~175	°C
Storage temperature range		T_{stg}	-55~150	°C

Thermal Characteristics

Characteristics	Symbol	Rating	Unit
Thermal resistance junction-to-ambient	$R_{th(j-a)}$	40	°C/W
Thermal resistance junction-to-case for IGBT	$R_{th(j-c)}$	0.55	
Thermal resistance junction-to-case for Diode	$R_{th(j-c)}$	0.9	

Ordering Information

Part Number	Marking	Temp. Range	Package	Packing	RoHS Status
MBQ50T65RFRTH	50T65RFR	-55~150°C	TO-247	Tube	Compliant

Electrical Characteristics ($T_{vj} = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions		Min	Typ	Max	Unit
Static Characteristics							
Collector-emitter breakdown voltage	BV_{CES}	$I_C = 1\text{mA}$, $V_{GE} = 0\text{V}$		650	-	-	V
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 50\text{A}$, $V_{GE} = 15\text{V}$	$T_{vj} = 25^\circ\text{C}$	-	1.85	2.40	V
			$T_{vj} = 175^\circ\text{C}$	-	2.60	-	
Diode forward voltage	V_F	$V_{GE} = 0\text{V}$, $I_F = 50\text{A}$	$T_{vj} = 25^\circ\text{C}$	-	2.20	2.70	V
			$T_{vj} = 175^\circ\text{C}$	-	2.27	-	
Gate-emitter threshold voltage	$V_{GE(th)}$	$V_{CE} = V_{GE}$, $I_C = 0.5\text{mA}$		3.8	5.0	6.2	V
Zero gate voltage collector current	I_{CES}	$V_{CE} = 650\text{V}$, $V_{GE} = 0\text{V}$		-	-	40	μA
Gate-emitter leakage current	I_{GES}	$V_{GE} = 20\text{V}$, $V_{CE} = 0\text{V}$		-	-	± 100	nA

Dynamic Characteristics

Total gate charge	Q_G	$V_{CE} = 520\text{V}$, $I_C = 50\text{A}$, $V_{GE} = 15\text{V}$	-	86	-	nC
Gate-emitter charge	Q_{GE}		-	21	-	
Gate-collector charge	Q_{GC}		-	38	-	
Input capacitance	C_{ies}	$V_{CE} = 25\text{V}$, $V_{GE} = 0\text{V}$, $f = 1\text{MHz}$	-	2440	-	pF
Output capacitance	C_{oes}		-	149	-	
Reverse transfer capacitance	C_{res}		-	38	-	

Switching Characteristics

Turn-on delay time	$t_{d(on)}$	$V_{GE} = -10/15\text{V}$, $V_{CC} = 400\text{V}$, $I_C = 50\text{A}$, $R_G = 10\Omega$, Inductive Load, $T_{vj} = 25^\circ\text{C}$	-	45	-	ns
Rise time	t_r		-	51	-	
Turn-off delay time	$t_{d(off)}$		-	53	-	
Fall time	t_f		-	22	-	
Turn-on switching energy	E_{on}	$V_{GE} = -10/15\text{V}$, $V_{CC} = 400\text{V}$, $I_C = 50\text{A}$, $R_G = 10\Omega$, Inductive Load, $T_{vj} = 175^\circ\text{C}$	-	1.36	-	mJ
Turn-off switching energy	E_{off}		-	0.49	-	
Total switching energy	E_{ts}		-	1.85	-	
Turn-on delay time	$t_{d(on)}$		-	46	-	ns
Rise time	t_r		-	51	-	
Turn-off delay time	$t_{d(off)}$		-	55	-	
Fall time	t_f		-	24	-	
Turn-on switching energy	E_{on}		-	1.67	-	mJ
Turn-off switching energy	E_{off}		-	0.56	-	
Total switching energy	E_{ts}		-	2.22	-	
Reverse recovery time	t_{rr}	$I_F = 50\text{A}$, $di_F/dt = 1000\text{A}/\mu\text{s}$, $T_{vj} = 25^\circ\text{C}$	-	135	-	ns
Reverse recovery current	I_{rr}		-	22	-	A
Reverse recovery charge	Q_{rr}		-	1.55	-	μC
Reverse recovery time	t_{rr}	$I_F = 50\text{A}$, $di_F/dt = 1000\text{A}/\mu\text{s}$, $T_{vj} = 175^\circ\text{C}$	-	197	-	ns
Reverse recovery current	I_{rr}		-	24	-	A
Reverse recovery charge	Q_{rr}		-	2.53	-	μC




Fig.1. Typical output characteristics($T_{vj}=25^{\circ}\text{C}$)




Fig.2. Typical output characteristics($T_{vj}=175^{\circ}\text{C}$)




Fig.3. Typical transfer characteristics




Fig.4. Typical collector-emitter saturation voltage-junction temperature




Fig.5. Diode forward characteristics




Fig.6. Diode forward voltage-junction temperature




Fig.7. Threshold voltage-junction temperature




Fig.8. Typical capacitance




Fig.9. Typical gate charge




Fig.10. Typical turn on times-collector current




Fig.11. Typical turn off times-collector current




Fig.12. Switching losses-collector current




Fig.13. Typical turn on times-gate resistance




Fig.14. Typical turn off times-gate resistance




Fig.15. Switching losses-gate resistance




Fig.16. Typical turn on times-junction temperature




Fig.17. Typical turn off times-junction temperature




Fig.18. Switching losses-junction temperature




Fig.19. IGBT transient thermal impedance




Fig.20. FRD transient thermal impedance




Fig.21. FBSOA





Fig.22. RBSOA

Physical Dimension

TO-247

Dimensions are in millimeters, unless otherwise specified



Dimension	Min(mm)	Max(mm)
A	4.70	5.31
A1	2.20	2.60
A2	1.50	2.49
b	0.99	1.40
b1	2.59	3.43
b2	1.65	2.39
c	0.38	0.89
D	20.30	21.46
D1	13.08	-
E	15.45	16.26
E1	13.06	14.02
E2	4.32	5.49
e	5.45BSC	
L	19.81	20.57
L1	-	4.50
ΦP	3.50	3.70
Q	5.38	6.20
S	6.15BSC	

Note: Package body size, length and width do not include mold flash, protrusions and gate burrs.



DISCLAIMER:

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Magnachip reserves the right to change the specifications and circuitry without notice at any time. Magnachip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Magnachip product.  Magnachip is a registered trademark of Magnachip semiconductor Ltd.