

Product Highlight

Features



- High switching speed with a low gate charge
- Fast intrinsic diode with low reverse recovery
- Robust Avalanche Capability
- 100% Avalanche Tested
- Pb-free, Halogen Free, and RoHS Compliant

Benefits

- System efficiency improvement
- Higher frequency applicability
- Increased power density
- Reduced cooling effort

Applications

- Solar inverter
- EV charging station
- UPS
- Industrial power supply



Key Parameters

$BV_{DSS, T_C=25^\circ C}$	$I_D, T_C=25^\circ C$	$R_{DS(on), typ}$	$Q_{g, typ}$
650 V	75 A	27 mΩ	91 nC



Package Marking and Ordering Information

Part Number	Top Marking	Package	Packing Method	Quantity
MSQS065R027T2TH	065R027T2	TO-247-4L	Tube	30 units

Absolute Maximum Ratings ($T_C = 25^\circ C$ unless otherwise noted)

Symbol	Parameter	Value	Unit
V_{DSS}	Drain to Source Voltage	650	V
V_{GS}	Gate to Source Voltage (DC)	-10 / +22	V
V_{GSop}	Recommended Operation Value	-5 / +18	V
I_D	Drain Current	Continuous ($T_C = 25^\circ C$)	75*
		Continuous ($T_C = 100^\circ C$)	53*
I_{DM}	Drain Current	Pulsed (Note1)	200*
P_D	Power Dissipation	($T_C = 25^\circ C$)	273
		Derate Above 25°C	1.82
T_J	Operating Temperature Range	-55 to 175	°C

*Limited by maximum junction temperature.

Note 1. Repetitive rating: pulse-width limited by maximum junction temperature.

1. Package

Temperature Ratings

Symbol	Parameter	Value	Unit
T_{STG}	Storage Temperature Range	-55 to 175	°C
T_L	Maximum Lead Temperature for Soldering, 1/8" from Case for 10 Seconds	260	°C

Thermal Characteristics

Symbol	Parameter	Value	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	0.55	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient, Max.	40	



2. MOSFET

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Off Characteristics						
BV_{DSS}	Drain to Source Breakdown Voltage	$V_{GS} = 0\text{ V}, I_D = 1\text{ mA}$	650			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS} = 650\text{ V}, V_{GS} = 0\text{ V}$		1	100	μA
		$V_{DS} = 650\text{ V}, V_{GS} = 0\text{ V}, T_J = 175^\circ\text{C}$		10		
I_{GSS}	Gate-Source Leakage Current	$V_{GS} = +22\text{ V}, V_{DS} = 0\text{ V}$			+100	nA
		$V_{GS} = -10\text{ V}, V_{DS} = 0\text{ V}$			-100	
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 11.7\text{ mA}$ (tested after $V_{GS} = 22\text{ V}, 1\text{ ms pulse}$)	1.8	2.8	4.5	V
$R_{DS(on)}$	Static Drain to Source On Resistance	$V_{GS} = 18\text{ V}, I_D = 35\text{ A}$		27	38	$\text{m}\Omega$
		$V_{GS} = 18\text{ V}, I_D = 35\text{ A}, T_J = 175^\circ\text{C}$		35		
g_{fs}	Transconductance	$V_{DS} = 20\text{ V}, I_D = 35\text{ A}$		25.9		S
Dynamic Characteristics						
C_{iss}	Input Capacitance	$V_{DS} = 400\text{ V}, V_{GS} = 0\text{ V}, f = 250\text{ kHz}$		1853		pF
C_{oss}	Output Capacitance			207		
C_{rss}	Reverse Capacitance			10.5		
E_{oss}	Stored Energy in Output Capacitance	$V_{DS} = 0\text{ V to } 400\text{ V}, V_{GS} = 0\text{ V}$		20.6		μJ
$C_{o(er)}$	Energy Related Output Capacitance			257		pF
$C_{o(tr)}$	Time Related Output Capacitance			372		
$Q_{g(tot)}$	Total Gate Charge	$V_{DS} = 400\text{ V}, I_D = 35\text{ A},$ $V_{GS} = -5\text{ V} / 18\text{ V},$ Inductive load		91		nC
Q_{gs}	Gate to Source Charge			25		
Q_{gd}	Gate to Drain "Miller" Charge			21		
R_G	Internal Gate Resistance	$f = 1\text{ MHz}$		3.0		Ω
Switching Characteristics						
$t_{d(on)}$	Turn-On Delay Time	$V_{DS} = 400\text{ V}, I_D = 35\text{ A},$ $V_{GS} = -5\text{ V} / 18\text{ V}, R_G = 5.6\text{ }\Omega,$ Inductive load		19		ns
t_r	Turn-On Rise Time			17		
$t_{d(off)}$	Turn-Off Delay Time			40		
t_f	Turn-Off Fall Time			8		
E_{on}	Turn-on Switching Energy			65		μJ
E_{off}	Turn-off Switching Energy			105		
E_{tot}	Total Switching Energy			170		







3. Body Diode

Electrical Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
Source-Drain Diode Characteristics						
I_S	Maximum Continuous Diode Forward Current				*75	A
I_{SM}	Maximum Pulsed Diode Forward Current				*200	
V_{SD}	Diode Forward Voltage	$V_{GS} = -5\text{ V}, I_{SD} = 35\text{ A}$		4.2		V
t_{rr}	Reverse Recovery Time	$V_{DD} = 400\text{ V}, I_{SD} = 35\text{ A},$ $di_F/dt = 1000\text{ A}/\mu\text{s},$ Includes Q_{OSS}		20		ns
Q_{rr}	Reverse Recovery Charge			141		nC
I_{rrm}	Peak Reverse Recovery Current			11.5		A

*Limited by maximum junction temperature.

4. Typical Performance Characteristics



4. Typical Performance Characteristics

Figure 7. Diode Forward Voltage Characteristics vs. Source-Drain Current $T_J = -40^\circ\text{C}$




Figure 8. Diode Forward Voltage Characteristics vs. Source-Drain Current $T_J = 25^\circ\text{C}$




Figure 9. Diode Forward Voltage Characteristics vs. Source-Drain Current $T_J = 125^\circ\text{C}$




Figure 10. Diode Forward Voltage Characteristics vs. Source-Drain Current $T_J = 175^\circ\text{C}$




Figure 11. Threshold Voltage vs. Temperature















Figure 12. Gate Charge Characteristics



4. Typical Performance Characteristics



4. Typical Performance Characteristics



5. Testing conditions

Figure 23. Inductive Load Switching Test Circuit and Waveforms






Figure 24. Peak Diode Recovery dv/dt Test Circuit and Waveforms



6. Package Outlines – TO-247-4L

* Dimensions in millimeters



SYMBOL	Common		
	DIMENSIONS MILLIMETER		
	MIN.	NOM.	MAX.
A	4.80	5.00	5.20
A1	2.29	2.42	2.54
A2	1.90	2.00	2.10
b	1.10	1.20	1.30
b1	1.86	2.01	2.15
c	0.50	0.60	0.70
D	20.90	21.00	21.10
D1	17.43	17.63	17.83
E	15.75	15.94	16.13
E1	13.46	13.66	13.86
E2	4.32	4.58	4.83
e	2.54 BSC.		
e1	5.08 BSC.		
L	19.80	19.95	20.10
L1	-	-	4.30
P	3.56	3.61	3.66
P1	6.75	6.80	6.85
Q	5.38	5.79	6.20
S	6.15 BSC.		