



AMDU040N015PSVRH

Single N-channel Trench MOSFET 40V 1.5mΩ

FEATURES



- Trench power MOSFET technology
- Single N-channel trench, normal gate level
- Enhanced avalanche ruggedness
- 100% Avalanche tested
- Maximum 175°C junction temperature

PRODUCT VALIDATION

- Qualified according to AEC-Q101 Standard

KEY PERFORMANCE PARAMETERS

V_{DS}	40	V
$R_{DS(on), typ.}$	0.0013	Ω
I_D	198	A
Q_g	43	nC
Junction temperature _{, max}	175	°C



ORDERING INFORMATION

Type / Ordering Code	Package	Marking	Packing	RoHS Status
AMDU040N015PSVRH	PDFN56	040N015P	Tape & Reel	Halogen Free

<http://www.magnachip.com>

ABSOLUTE MAXIMUM RATINGS, at $T_c = 25^\circ\text{C}$, unless otherwise specified

Parameter		Symbol	Rating	Unit
Drain-source Voltage		V_{DS}	40	V
Gate-source Voltage		V_{GS}	± 20	
Drain current	$T_c=25^\circ\text{C}$ (Silicon Limited)	I_D	198	A
	$T_c=25^\circ\text{C}$ (Package Limited)		135	
	$T_c=100^\circ\text{C}$ (Silicon Limited)		140	
¹⁾ Pulsed drain current	$T_c=25^\circ\text{C}$, $t_p \leq 100 \mu\text{s}$	I_{DM}	630	
Total power dissipation	$T_c=25^\circ\text{C}$	P_{tot}	100	W
	$T_c=100^\circ\text{C}$		50	
²⁾ Avalanche energy, single pulse		E_{AS}	240	mJ
Operating and storage temperature		T_j, T_{stg}	- 55 ~ 175	$^\circ\text{C}$

THERMAL CHARACTERISTICS

Parameter	Symbol	Rating	Unit
Thermal resistance, junction - case	$R_{\theta JC}$	1.5	$^\circ\text{C/W}$
³⁾ Thermal resistance, junction - ambient	$R_{\theta JA}$	50	

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ\text{C}$)**STATIC CHARACTERISTICS**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Drain-source breakdown voltage	$V_{(BR)DSS}$	40	-	-	V	$V_{GS}=0\text{ V}$, $I_D=250\text{ }\mu\text{A}$
Gate threshold voltage	$V_{GS(th)}$	2.25	-	3.75		$V_{DS}=V_{GS}$, $I_D=241\text{ }\mu\text{A}$
Zero gate voltage drain current	I_{DSS}	-	-	1	μA	$V_{DS}=40\text{ V}$, $V_{GS}=0\text{ V}$
Gate-source leakage current	I_{GSS}	-	-	± 100	nA	$V_{GS}=\pm 20\text{ V}$, $V_{DS}=0\text{ V}$
Drain-source on-state resistance	$R_{DS(on)}$	-	1.30	1.50	m Ω	$V_{GS}=10\text{ V}$, $I_D=50\text{ A}$
		-	1.42	2.20		$V_{GS}=8\text{ V}$, $I_D=50\text{ A}$
⁴⁾ Gate resistance	R_g	-	1.2	-	Ω	$f=1\text{ MHz}$
⁴⁾ Transconductance	g_{fs}	-	110	-	S	$V_{DS}=10\text{ V}$, $I_D=50\text{ A}$

⁴⁾ DYNAMIC CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Input capacitance	C_{iss}	-	3248	-	pF	$V_{GS}=0\text{ V}$, $V_{DS}=20\text{ V}$, $f=1\text{ MHz}$
Output capacitance	C_{oss}	-	889	-		
Reverse transfer capacitance	C_{rss}	-	29	-		
Turn-on delay time	$t_{d(on)}$	-	21	-	ns	$V_{DD}=20\text{ V}$, $V_{GS}=10\text{ V}$, $I_D=50\text{ A}$, $R_{G,ext}=3\text{ }\Omega$
Rise time	t_r	-	9	-		
Turn-off delay time	$t_{d(off)}$	-	37	-		
Fall time	t_f	-	7	-		

⁴⁾ GATE CHARGE CHARACTERISTICS

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
Gate to source charge	Q_{gs}	-	14	-	nC	$V_{DD}=32\text{ V}$, $I_D=50\text{ A}$, $V_{GS}=0\text{ to }10\text{ V}$
Gate charge at threshold	$Q_{gs(th)}$	-	5	-		
Gate to drain charge	Q_{gd}	-	6	-		
Switching charge	Q_{sw}	-	15	-		
Gate charge total	Q_g	-	43	-		
Gate plateau voltage	$V_{plateau}$	-	5	-	V	

SOURCE-DRAIN DIODE

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions / Note
⁴⁾ Diode continuous forward current	I_S	-	-	135	A	-
⁴⁾ Diode pulse current	$I_{S,pulse}$	-	-	630		pulsed; $t_p \leq 100\text{ }\mu\text{s}$
Diode forward voltage	V_{SD}	-	0.82	1.0	V	$V_{GS}=0\text{ V}$, $I_F=50\text{ A}$
⁴⁾ Reverse recovery time	t_{rr}	-	38	-	ns	$I_F=50\text{ A}$, $di_F/dt=100\text{ A}/\mu\text{s}$
⁴⁾ Reverse recovery charge	Q_{rr}	-	44	-	nC	

Notes

1. Pulse width limited by T_{Jmax}
2. Starting $T_J=25^\circ\text{C}$, $L=1\text{ mH}$, $I_{AS}=21.9$, $V_{DD}=36\text{ V}$, $V_{GS}=10\text{ V}$
3. Surface mounted FR-4 board by JEDEC (jesd51-7)
4. The parameter is not subject to production testing - guaranteed by design.

ELECTRICAL CHARACTERISTICS DIAGRAMS




Fig. 1. Typ. Output Characteristics




Fig. 2. Typ. Drain-Source On-Resistance




Fig. 3. On-Resistance vs. Junction Temperature




Fig. 4. On-Resistance vs. Gate-Source Voltage




Fig. 5. Typ. Transfer Characteristics




Fig. 6. Forward Characteristics of Reverse Diode

ELECTRICAL CHARACTERISTICS DIAGRAMS




Fig. 7. Typ. Gate Charge




Fig. 8. Typ. Capacitance




Fig. 9. Safe Operating Area




Fig. 10. Drain Current vs. Temperature





Fig. 11. Transient Thermal Impedance

Fig. 12. $V_{GS(th)}$ Variation with Temperature

ELECTRICAL CHARACTERISTICS DIAGRAMS




Fig. 13. BV_{DSS} Variation with Temperature





Fig. 14. Power Dissipation

Package Outlines

PDFN56



Symbol	Dimension (mm)		
	Min	Nom	Max
A	0,90	–	1,10
b	0,33	–	0,51
C	0,20	–	0,34
D	4,50	–	5,30
D1	4,50	–	5,10
D2	3,61	–	4,22
E	5,90	–	6,30
E1	5,50	–	6,10
E2	3,38	–	4,30
e	1,27 BSC		
H	0,41	–	0,71
K	0,20	–	–
L	0,51	–	0,71
L1	0,06	–	0,20
a	0°	–	12°

Notes

Package body size, length and width do not include mold flash, protrusions and gate burrs.

DISCLAIMER :

The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. Seller's customers using or selling Seller's products for use in such applications do so at their own risk and agree to fully defend and indemnify Seller.

Magnachip reserves the right to change the specifications and circuitry without notice at any time. Magnachip does not consider responsibility for use of any circuitry other than circuitry entirely included in a Magnachip product.  Magnachip is registered trademarks of Magnachip Semiconductor Ltd.